

A look at Moment-based approaches in imaging part 4: Some applications

Shu Huazhong^{1 2}, Luo Limin^{1 2}, Coatrieux Jean-Louis^{2 3 *}

¹ LIST, Laboratory of Image Science and Technology SouthEast University, Si Pai Lou 2, Nanjing, 210096, CN

² CRIBS, Centre de Recherche en Information Biomédicale sino-français INSERM : Laboratoire International Associé, Université Rennes I, SouthEast University, Nankin, CN

³ LTSI, Laboratoire Traitement du Signal et de l'Image INSERM : U642, Université Rennes I, Campus de Beaulieu, 263 Avenue du Général Leclerc - CS 74205 - 35042 Rennes Cedex, FR

* Correspondence should be addressed to: Jean-Louis Coatrieux <jean-louis.coatrieux@univ-rennes1.fr>

They all work in the «Centre de Recherche en Information Biomédicale Sino-Français (CRIBS)»

MESH Keywords Algorithms ; Image Enhancement ; methods ; Image Interpretation, Computer-Assisted ; methods ; Signal Processing, Computer-Assisted

This last paper of this series provides a survey of the topics the moments have addressed in image processing at large. Our introductory papers dealt with the theoretical expressions of orthogonal and non-orthogonal basis functions [1], with important properties like geometric invariance, robustness to noise or blurring [2] and the computational accuracy and complexity [3]. Here, most of the steps going from image reconstruction, segmentation, motion tracking to pattern recognition are examined through moment-based techniques. Though they have not an equal importance in this wide spectrum of applications, they can offer sound solutions. Rather than entering into methodological details and examples, this paper is intended to identify the main contributions brought by moments.

Featuring Image analysis

The multiple applications of digital images lead to segment the field into many areas, each having their own journals and conferences. This diversity makes more difficult to have a full view on the on-going research and may hide the general interest of a given method. It must be first pointed out that the physical process underlying the image formation is of major importance for the all subsequent processing. If not properly dealt with, most of the information later extracted can be biased. The reconstruction problem, so important in medical imaging, can be dealt with purely mathematical views but the capability to model and control the acquisition device should open new pathways. Conversely, the search for generic algorithms, a major trend in image analysis, is attractive: the efficiency of such approach has been demonstrated through many examples. Assumptions are always required however and they must be adapted to the situations under study. Thus, a full apprehension of the field has to take into account the 4-tuple, “observations (or data), objects (properties), goals (analysis objectives), methods (algorithms)”.

Multidimensional observations are more and more available in medicine (volume (3-D) images, 2-D+t and 3-D+t image sequences, with scalar or vectorial descriptions). The spatial and temporal sampling is here critical according to the task to be carried out. The huge data sets they provide (hundreds of slices or 2-D projections) call for challenging time computations. The objects of interest are varying in shape among individuals and with disorders, may change and deform over time, have poor contrast. Moreover, they are not reducible to simple geometric patterns. These difficulties may be compensated by introducing some, but limited, interactive pointing or delineation. The ultimate goal (omitting the image formation) is to provide the user with relevant features for clinical decision and therapeutic guidance. It includes parameters for quantifying the lesion extent and discriminating them, locating the abnormal patterns in anatomical space, or characterizing the behavior in space and time. The methods that may bring answers to these issues are many. The classical paradigms like low vs high level, data-driven vs model-driven, salient feature and primitive grouping, edge and region cooperation, local vs global analysis, image understanding through semantic labeling and spatial relation modeling, etc. are still of value in most of the problems to solve. Non-stationary noise and artifacts, low contrast, object occlusions and deformations, variability in observation conditions, etc. lead to recurrent challenges in computer vision when robustness, accuracy, completeness must be achieved under real-time constraints.

The main applications

Reconstruction

This issue has received much attention in the medical imaging literature. A number of imaging modalities are concerned from X-ray computerized tomography and emission tomography up to acoustic and optical techniques. They all bring different insights in the human body either morphological or functional. Recent works deal with reconstruction from only limited range projections with the aim to estimate the projections at unknown views such as the moment-based approaches reported by Salzman [4] and Goncharev [5]. Milanfar et al. [6] presented a variational framework for the tomographic reconstruction of an image from the maximum likelihood estimates of its orthogonal moments. Basu

and Bresler [7, 8] investigated the problem of recovering the view angles from the projection data by means of moment method. Rouze et al. [9] derived a relation between Zernike moments and the Radon transform, and then applied it to reconstruction. By establishing a relationship between the image geometric moments and projection moments, Wang and Sze [10] presented an approach to reconstruct the CT images from limited range projections. Shu et al. [11] extended Wang's method using the orthogonal Legendre moments to improve the quality of the reconstructed image. The advantage of Shu's method is that the orthogonal moments have simple inverse transform, thus, the image can be more easily obtained from the orthogonal moments. Moreover, the geometric moments, especially at high order, are sensitive to noise and digitization error. However, both methods were based on the use of continuous moments. When applied to 2-D digital images, the double integrals are usually approximated by discrete summations that lead to numerical errors in the computed moments. The discrete orthogonal moments, in particular Tchebichef moments, do not require any discrete approximation for numerical implementation and moreover the discrete orthogonal Tchebichef polynomials are the simplest among all the discrete orthogonal polynomials with a definition domain ideally suited for square images [12]. However, the traditional Radon transform is no longer applicable, and a discrete version of Radon transform is required. Beylkin [13] described a discrete Radon transform (DRT) to map a set of sampled image points onto a set of discrete projections. The algebraic mapping for this transformation can be computed exactly, since no interpolation of the data is required. Matus and Flusser [14] developed a group theoretic and Fourier based approach to the DRT. Svalbe [15] and Kingston [16] derived improved versions of DRT to handle both continuous projections and discrete projections in Fourier and Radon space. The advantage of the techniques reported in [15] and [16] is that they require a straightforward 1-D linear interpolation, a simple sorting of projection samples and no pre-processing of the projection data. The purely mathematical views provided by moments for the reconstruction problem have a drawback: the difficulties they have to deal with the physical characteristics inherent to any image capture.

Pattern Recognition

This topic represents certainly the major applications of moments and a survey of the all literature is out of reach in a short paper. The classical views regarding pattern recognition rely on the ability to extract the objects of interest, on the choice of their representation and the final decision step, e.g. allocation to classes. These classes may be formed beforehand through a learning phase. Many techniques are available to manage that either by contour-based or region-based features with local or global descriptions. They can operate in the image or in the transform domains. They include kernel methods (like Support Vector Machine), neural networks, rigid or elastic matching, string coding and matching, etc. They all require a distance measure to estimate the similarity between two shapes. The flexibility of moments in dealing with binary or grey level images, polygonal and region representations on one hand and, in the other hand, the invariance properties discussed in [2] make them particularly attractive for a number of applications. They offer compact and robust descriptions and bring statistical cues on pixel (or voxel) value distributions: in some cases (the low orders) they have physical interpretations.

Invariance properties are central for pattern recognition as discussed in [2] [17]. Many attempts have been reported using moments for aircraft recognition [18], identification of building and bridge [19], partially occluded object localization [20], flower shape analysis [21], image retrieval [22], character recognition [23–27]. Bailey and Srinath [28] investigated invariant character recognition using Legendre, Zernike and pseudo-Zernike moments with different classifiers. Khotanzad and Hong [29] has shown that a neural network classifier using Zernike moments has a strong class separability power. The evolution towards images with higher dimensions (3-D and n-D) has also motivated a lot of theoretical works [30–36].

Beyond shape features, texture patterns are also of interest in order to recognize objects. Less moment-based works have been devoted to texture analysis [37, 38]. The attempts made for tissue characterization did not however show a significant breakthrough: this can be due to the texture complexity, resulting from mixture of structural tissue properties, partial volume effects, noise and reconstruction artefacts.

Miscellaneous

We briefly review here some additional topics where the moments have been called for but with limited impact. As pointed out above, nearly every system is initialized by detection and segmentation tasks. Despite the recent achievements provided by deformable models, level set and graph-cut methods, these problems remain open in medical applications and require some user interaction. Edge detection is mainly carried out by derivative operators while integrative schemes may offer a sound alternative as shown in 2-D with geometric moments [39] or Zernike moments [40]. Geometric and Legendre moments have also been proposed for 3-D surface detection assuming a local planar patch [41] or a parabolic model [42]. Image registration or alignment is another active area. Most approaches rely on establishing the feature correspondence between a reference image and the target image, a task that can be dealt with moments [43–50]. Motion estimation is another major area in image analysis [51]. Optical flow methods based on differential-geometric descriptors and matching techniques (or correlation) have been widely explored. Joint motion-tracking approaches combining different types of information (boundary-region) and different sources (gradient, intensity, motion) in scenes with multiple objects should provide new perspectives. Moments have not received much attention in this area and the few attempts made were essentially focused on optical flow methods using Zernike moments [52, 53].

Conclusion

Moment-based methods are still marginal in image processing and it is our hope that this series will motivate new research on this topic and open new applications especially in medical imaging. These techniques cover, as we pointed out, a wide spectrum of applications and deserve to be confronted to other attractive and competitive methods. They should also be combined in order to take advantage of their basic features, in particular the invariance properties and the continuously improvements in computational complexity.

References:

1. Shu HZ, Luo LM, Coatrieux JL Moment-based approaches in image, Part 1: basic features. *IEEE Eng Med Biol Mag.* 26: (5) 70- 75 2007;
2. Shu HZ, Luo LM, Coatrieux JL Moment-based approaches in image, Part 2: invariance. *IEEE Eng Med Biol Mag.* 27: (1) 81- 83 2008;
3. Shu HZ, Luo LM, Coatrieux JL Moment-based approaches in image, Part 3: computational considerations. *IEEE Eng Med Biol Mag.* 27: (3) 89- 91 2008;
4. Salzman D A method of general moments for orienting 2D projections of unknown 3D objects. *Comput Vis Graph Image Process.* 50: (2) 129- 156 1990;
5. Goncharev AB Methods of integral geometry and recovering a function with compact support from its projections in unknown directions. *Acta Appl Math.* 11: (3) 213- 222 1988;
6. Milanfar PM, Karl WC, Willsky AS A moment-based variational approach to tomographic reconstruction. *IEEE Trans Image Process.* 5: (3) 459- 470 1996;
7. Basu S, Bresler Y Uniqueness of tomography with unknown view angles. *IEEE Trans Image Process.* 9: (6) 1094- 1106 2000;
8. Basu S, Bresler Y Feasibility of tomography with unknown view angles. *IEEE Trans Image Process.* 9: (6) 1107- 1122 2000;
9. Rouze NC, Soon VC, Hutchins GD On the connection between the Zernike moments and Radon transform of an image. *Pattern Recognit Lett.* 27: (6) 636- 642 2006;
10. Wang TJ, Sze TW The image moment method for the limited range CT image reconstruction and pattern recognition. *Pattern Recognit.* 34: (11) 2145- 2154 2001;
11. Shu HZ, Zhou J, Han GN, Luo LM, Coatrieux JL Image reconstruction from limited range projections using orthogonal moments. *Pattern Recognit.* 40: (2) 670- 680 2007;
12. Dai XB, Shu HZ, Luo LM, Han GN, Coatrieux JL Reconstruction of tomographic image from limited range projections using discrete Radon transform and Tchebichef moments. *IEEE Trans Image Process.*
13. Beylkin G Discrete Radon transform. *IEEE Trans Acoustics Speech Signal Process.* 35: (2) 162- 172 1987;
14. Matus F, Flusser J Image representation via a finite radon transform. *IEEE Trans Pattern Anal Machine Intell.* 15: (10) 996- 1106 1993;
15. Svalbe I, van der Spek Dimitri Reconstruction of tomographic images using analog projections and the digital radon transform. *Linear Algebra and Its Applications.* 339: (1) 125- 145 2001;
16. Kingston A, Svalbe I Mapping between digital and continuous projections via the discrete radon transform in Fourier space. *DICTA'03; Sydney* 1- 10 Dec 2003;
17. Hu M Visual pattern recognition by moment invariant. *IRE Trans Inform Theory.* 8: (2) 179- 187 1962;
18. Dudani SA, Breeding SK, McGhee R Aircraft identification by moment invariants. *IEEE Trans Comput.* 26: (1) 39- 45 1977;
19. Gilmore JF, Boyd WW Building and bredge classification by invariant moments. *Proc SPIE.* 292: 256- 263 1981;
20. Sluzek A Using moment invariants to recognize and locate partially occluded 2D objects. *Pattern Recognit Lett.* 7: (4) 253- 257 1988;
21. Miao ZJ Zernike moment-based image shape analysis and its application. *Pattern Recognit Lett.* 21: (2) 169- 177 2000;
22. Kim WY, Kim YS A region-based shape descriptor using Zernike moments. *Signal Processing: Image Communication.* 16: (1-2) 95- 102 2000;
23. Fang M, Hausler G Class of transforms invariant under shift, rotation, and scaling. *Appl Opt.* 29: (5) 704- 708 1990;
24. Reiss TH The revised fundamental theorem of moment invariants. *IEEE Trans Pattern Anal Mach Intell.* 13: (8) 830- 834 1991;
25. Shen L, Sheng Y Noncentral image moments for invariant pattern recognition. *Opt Eng.* 34: (11) 3181- 3186 1995;
26. Gruhn M, Hsu KY Moment-based image normalization with high noise tolerance. *IEEE Trans Pattern Anal Machine Intell.* 19: (2) 136- 139 1997;
27. Kan C, Srinath MD Invariant character recognition with Zernike and orthogonal Fourier-Mellin moments. *Pattern Recognit.* 35: (1) 143- 154 2002;
28. Bailey RR, Srinath MD Orthogonal moment features for use with parametric and non-parametric classifiers. *IEEE Trans Pattern Anal Machine Intell.* 18: (4) 389- 399 1996;
29. Khotanzad A, Hong YH Classification of invariant image representations using a neural network. *IEEE Trans Acoust Speech Signal Process.* 38: (6) 1028- 1938 1990;
30. Sadjadi FA, Hall EL Three-dimensional moment invariants. *IEEE Trans Pattern Anal Machine Intell.* 2: (2) 127- 136 1980;
31. Lo CH, Don HS 3-D moment forms: their construction and application to object identification and positioning. *IEEE Trans Pattern Anal Machine Intell.* 11: (10) 1053- 1064 1989;
32. Canterakis N 3D Zernike moments and Zernike affine invariants for 3D image analysis and recognition. *Proc of 11th Scandinavian Conference on Image Analysis.* 85- 93 1999;
33. Novotni M, Klein R Shape retrieval using 3D Zernike descriptors. *Comput Aided Design.* 36: (11) 1047- 1062 2004;
34. Mamistvalov AG N-dimensional moment invariants and conceptual mathematical theory of recognition n-dimensional solids. *IEEE Trans Pattern Anal Machine Intell.* 20: (8) 819- 831 1998;
35. Flusser J, Boldys J, Zivova B Moment forms invariant to rotation and blur in arbitrary number of dimensions. *IEEE Trans Pattern Anal Machine Intell.* 25: (2) 234- 246 2003;
36. Xu D, Li H Geometric moment invariants. *Pattern Recognit.* 41: (1) 240- 249 2008;
37. Tuceryan M Moment based texture segmentation. *Pattern Recognit Lett.* 15: (7) 659- 667 1994;
38. Wang J, Healey G Using Zernike moments for the illumination and geometry invariant classification of multispectral texture. *IEEE Trans Image Process.* 7: (2) 196- 203 1998;
39. Luo LM, Xie XH, Bao XD A modified moment-based edge operator for rectangular pixel image. *IEEE Trans Circ Sys Video Tech.* 4: (6) 552- 554 1994;
40. Ghosal S, Mehrotra R Orthogonal moment operators for subpixel edge detection. *Pattern Recognit.* 26: (2) 295- 306 1993;
41. Luo LM, Hamitouche C, Dillenseger JL, Coatrieux JL A moment-based three-dimensional edge operator. *IEEE Trans Biomed Eng.* 40: (7) 693- 703 1993;
42. Zhang H, Shu HZ, Luo LM, Dillenseger JL A Legendre orthogonal moment based 3D edge operator. *Science in China Ser G.* 48: (1) 1- 13 2005;
43. Wong RY, Hall EL Scene matching with invariant moments. *Comput Vis Graph Image Process.* 8: (1) 16- 24 1978;
44. Yang XH, Birkfellner W, Niederer P A similarity based on Tchebichef moments for 2D/3D medical image registration. *International Congress Series.* 1268: 153- 158 2004;
45. Liu J, Zhang TX Matching and normalization of affine deformed image from regular moments. *Pattern Recognit Lett.* 25: (14) 1619- 1631 2004;
46. Heikkila J Pattern matching with affine moment descriptors. *Pattern Recognit.* 37: (9) 1825- 1834 2004;
47. Yang Z, Cohen FS Cross-weighted moments and affine invariants for image registration and matching. *IEEE Trans Pattern Anal Machine Intell.* 21: (8) 804- 814 1999;
48. Rothe I, Susse H, Voss K The method of normalization to determine invariants. *IEEE Trans Pattern Anal Machine Intell.* 18: (4) 366- 376 1996;
49. Dong L, Boyer AL A portal image alignment and patient setup verification procedure using moments and correlation techniques. *Phys Med Biol.* 41: (4) 697- 723 1996;
50. Shu HZ, Ge Y, Luo LM, Wang JW, Yu WX, Bao XD An orthogonal moment-based method for automatic verification of radiation field shape. *Phys Med Biol.* 45: (10) 2897- 2911 2000;
51. Coatrieux JL Shape and function from motion in biomedical imaging: part 3. *IEEE Eng Med Biol Mag.* 26: (3) 81- 83 2007;
52. Ghosal S, Mehrotra R Robust optical flow estimation using semi-invariant local features. *Pattern Recognit.* 30: (2) 229- 237 1997;
53. Gu J, Luo LM, Shu HZ A local optimization algorithm for computing 2D optical flow field of heart echocardiograph image using Zernike moments. *Acta Electronic Sinica.* 29: (3) 350- 353 2001;