

Rapid SARS-CoV-2 inactivation by mercury and LED UV-C lamps on different surfaces

Marianne Maquart, Julien Marlet

► To cite this version:

Marianne Maquart, Julien Marlet. Rapid SARS-CoV-2 inactivation by mercury and LED UV-C lamps on different surfaces. Photochemical & Photobiological Sciences , 2022, Online ahead of print. 10.1007/s43630-022-00292-2 . inserm-03761842

HAL Id: inserm-03761842 https://inserm.hal.science/inserm-03761842v1

Submitted on 26 Aug 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Rapid SARS-CoV-2 inactivation by mercury and LED UV-C lamps on different surfaces

Marianne Maquart, Julien Marlet

▶ To cite this version:

Marianne Maquart, Julien Marlet. Rapid SARS-CoV-2 inactivation by mercury and LED UV-C lamps on different surfaces. Photochemical & Photobiological Sciences , Springer, 2022, pp.1-5. 10.1007/s43630-022-00292-2. inserm-03761842

HAL Id: inserm-03761842 https://www.hal.inserm.fr/inserm-03761842

Submitted on 26 Aug 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



1	Rapid SARS-CoV-2 inactivation by mercury and LED UV-C lamps on different surfaces
2	Running title: Rapid SARS-CoV-2 inactivation by UV-C
3	Marianne Maquart ¹ , Julien Marlet ^{1, 2}
4	¹ INSERM U1259 MAVIVH, Université de Tours, Tours, 37000, France
5	² Service de Bactériologie-Virologie-Hygiène, CHRU de Tours, Tours, 37000, France
6	
7	Corresponding author: Julien Marlet, julien.marlet@univ-tours.fr , +33 2 47 36 61 27
8	
9	ABSTRACT (99 words)
10	SARS-CoV-2 remains infectious for several hours on surfaces. It can be inactivated by UV-C
11	irradiation, but optimal conditions for rapid inactivation on non-plastic surfaces remains
12	unclear. We demonstrated that efficient SARS-CoV-2 inactivation (\geq 99.8 %) can be achieved
13	by both a UV-C mercury lamp and a UV-C LED in less than 30 seconds. Inactivation on a
14	plastic surface was more efficient with the mercury UV-C lamp (p<0.0001). SARS-CoV-2
15	inactivation levels were > 99.999 % on plastic, \ge 99.8 % on steel, tissue, paper and cardboard
16	after irradiation by both lamps at a distance of 3 cm during 30 sec.
17	
18	Key words: SARS-CoV-2, irradiation, UV-C, LED, mercury lamp, inactivation
10	

20 MANUSCRIPT (1636 words)

21 BACKGROUND

The human coronavirus named SARS-CoV-2 is a Betacoronavirus identified for the first time 22 23 in late 2019 in Wuhan, China and is now responsible for a major pandemic worldwide. This virus is transmitted mainly via respiratory droplets and also by direct contact with symptomatic 24 25 or asymptomatic patients or with contaminated surfaces [1]. SARS-CoV-2 can remain 26 infectious for up to 72 h on non-absorbent surfaces like plastic or steel and up to 24 h on 27 absorbent surfaces like cardboard [1]. UV-C irradiation (200-280 nm) is an effective disinfection approach to inactivate pathogens on surfaces, especially when detergents are not 28 29 suitable (electronic devices or water treatment). UV-C have a strong germicidal activity, 30 particularly at 265 nm, the maximal wavelength of absorption for nucleic acids [2]. They 31 inactivate pathogens by inducing the formation of pyrimidine dimers, thus inhibiting the 32 genome replication [2,3]. UV-C can inactivate SARS-CoV-2 on plastic or wood surfaces in a 33 few seconds or minutes but have not been evaluated on cardboard or paper [4-8]. UV-C 34 irradiation can be performed with UV light-emitting diodes (UV LEDs) or classical mercury 35 lamps [2]. UV LEDs allow more flexibility due to their small size, their low power consumption 36 and their specific emission wavelengths. Our objective was to evaluate the efficiency of a UV-C mercury lamp and a UV-C LED for the inactivation of SARS-CoV-2 on non-absorbent 37 38 (plastic, steel) and absorbent surfaces (tissue, paper and cardboard).

39

40 METHODS

41 Cell culture and virus

42 Vero cells (ATCC, CCL-81) and Vero-E6 cells (ATCC, CRL-1586) were maintained in
43 DMEM medium supplemented with 10% FCS and 1% penicillin-streptomycin at 37 °C, under
44 an atmosphere containing 5% CO₂. A clinical isolate of SARS-CoV-2 was isolated from a

45 nasopharyngeal swab collected from a patient suffering from COVID-19 at the Tours 46 University Hospital. The virus was amplified using Vero cells expressing Transmembrane 47 Protease Serine 2 (TMPRSS2). Viral titer was determined on Vero-E6 cells by the 50% tissue 48 culture infective dose (TCID₅₀) as previously described [9]. A viral stock of 3.10^5 TCID₅₀/mL 49 was prepared and stored at – 80 °C.

50 UV-C lamps

51 The first UV-C lamp was the Puritec HNS-L 2G11 UV-C germicidal mercury lamp (OSRAM, 52 Rosny-sous-bois, France), emitting at 254 nm and 185nm with a nominal wattage of 18 W. 53 Lamp dimensions were 31.5 cm x 4 cm. The second UV-C lamp was the KL265-50V-SM-WD UV-C LED (Klaran, Green Island, USA), emitting at 265 nm and consuming 70 mW of power. 54 55 LED dimensions were 3.5 x 3.5 mm. Irradiations were performed at 3, 5 or 10 cm with the lamp 56 positioned directly above the irradiated well for durations of 5, 15, 30 or 60 seconds. UV-C 57 doses received by the sample was measured with an optometer X1-5 (Gigahertz-Optik, GmbH). 58 UV-C doses (254 nm) received by the sample after irradiation with the mercury lamp at 3, 5 and 10 cm were 12.6 mJ/s/cm², 6.6 mJ/s/cm² and 2.6 mJ/s/cm², respectively. UV-C doses (265 59 60 nm) received by the sample after irradiation with the LED at 3, 5 and 10 cm were 2.6 mJ/s/cm², 61 1.34 mJ/s/cm² and 0.68 mJ/s/cm², respectively.

62 Quantification of SARS-CoV-2 inactivation after UV-C irradiation

The SARS-CoV-2 inoculum (200 μ L at 3.10⁵ TCID₅₀/ml) was deposited on relevant surfaces in 12-wells plates. Plastic (bottom of the well), steel (1 cm² steel ring), tissue (1 cm² punch of cotton cloth), paper (1 cm² punch of 80 g/m² white paper) and cardboard (1 cm² punch of solid unbleached board) were used in this experiment. After 5 minutes of contact with the surface, viruses were exposed to UV-C irradiation at 3, 5 or 10 cm for 5, 15, 30 or 60 seconds. Viable viruses were collected by a 5 min elution in 200 μ L of infection medium and directly deposited on Vero-E6 cells (MOI of 0.1). These cells had previously been plated at 3.10⁵ cells / well in 12-wells plates, 24 h before the experiment. After 1 h of infection, the viral suspension was removed, the cells were washed with 500 µL of PBS and 1ml of infection medium was added to each well. Twenty-four hours later, the supernatant was collected and the viral titer was determined by endpoint dilution and calculation of the TCID₅₀. All measurements were performed in duplicate in three independent experiments. SARS-CoV-2 inactivation (%) was calculated as follow: Inactivation (%) = $(1 - \frac{TCID50 \ after UV}{TCID50 \ before UV})*100$

SARS-CoV-2 inactivation efficiencies were compared between different UV-C sources,
different distance and different durations of irradiation, using the Mann-Whitney (two groups)
or the two-way ANOVA tests (more than two groups) with the GraphPad 9 software.

79

80 **RESULTS**

81 SARS-CoV-2 inactivation by UV-C on a plastic surface

No viable virus was detected after irradiation with the mercury UV-C lamp, even for low UV-82 C doses (12.6 mJ/cm²) (Figure 1A). This corresponded to a $6-\log_{10}$ decrease in SARS-CoV-2 83 84 TCID₅₀. Low doses of UV-C LED light (3.4 to 13 mJ/cm²) were associated with a 4-log₁₀ 85 reduction in SARS-CoV-2 TCID₅₀. Increased doses of LED UV-C light were associated with a 86 slower decrease in SARS-CoV-2 TCID₅₀ (Figure 1A). We searched for the optimal distances 87 (3, 5 or 10 cm) and durations (5, 15, 30 or 60 seconds) of UV-C irradiation for SARS-CoV-2 inactivation on a plastic surface. SARS-CoV-2 inactivation by the UV-C mercury lamp was > 88 89 99.999 % in all conditions regardless of the distance or duration of irradiation (Figure 1B). In 90 contrast, high level SARS-CoV-2 inactivation by the UV-C LED (> 99.999 %) required a close 91 position of the lamp (3 or 5 cm) and longer irradiations (\geq 15 seconds) (Figure 1B). The mercury 92 UV-C lamp was associated with higher SARS-CoV-2 inactivation rates in all conditions (Figure 1B), even when considering similar UV-C doses (3.4 to 156 mJ/cm², p<0.0001) (Figure 1A). 93

94 SARS-CoV-2 inactivation on steel, tissue, paper and cardboard

95 In light of previous results, SARS-CoV-2 inactivation by the UV-C lamps on steel, tissue, paper and cardboard was quantified after 15, 30 and 60 seconds of irradiation at a single distance of 96 97 3 cm (Figure 2B). These conditions corresponded to UV-C doses between 189 to 756 mJ/cm² for the mercury lamp and 39 to 156 mJ/cm² for the LED. No viable virus was detected after 98 99 irradiation with the mercury or the LED UV-C lamp on a steel surface (Figure 2A). In contrast, 100 viable viruses were still detected after irradiation with the mercury or the LED UV-C lamp on 101 absorbent surfaces (tissue, paper or cardboard) (Figure 2A). In contrast with the plastic surface, 102 there were no differences in inactivation rates between both lamps on absorbent surfaces (p =103 0.31, Figure 2A). SARS-CoV-2 inactivation was \geq 99.8 % on steel, tissue, paper and cardboard after irradiation by a UV-C mercury lamp or a UV-C LED, at a distance of 3 cm during 30 sec. 104 This condition corresponded to 378 and 78 mJ/cm² for the mercury and LED UV-C lamps, 105 106 respectively (Figure 2B). Short irradiation times (15 seconds) were less effective (90-99 % 107 inactivation, p < 0.05) on absorbent surfaces (Figure 2B).

108

109 **DISCUSSION**

Efficient inactivation of SARS-CoV-2 on contaminated surfaces (> 99.999 % on plastic and ≥ 110 111 99.8 % on steel, tissue, paper and cardboard) can be achieved by both the UV-C mercury lamp 112 and the UV-C LED at a distance of 3 cm during 30 sec. No viable virus was detected after 113 irradiation with the mercury UV-C lamp for a UV-C dose of 12.6 mJ/cm² (10 cm, 5 s), which is in line with most previous studies [8,10,11]. Few studies described lower performances for 114 other mercury lamps [4,12]. This irradiation (12.6 mJ/cm²) corresponded to a 6-log₁₀ decrease 115 in SARS-CoV-2 TCID₅₀, rarely observed with other mercury lamps for comparable UV-C 116 117 doses (3 to 5.5-log₁₀ decrease) [8,10–12]. These other studies were probably limited more by a 118 lower infectious titer of the viral inoculum than by the performances of the mercury lamps, 119 because no viable viruses were detected after irradiation [8,10,11]

A 4-log₁₀ reduction in SARS-CoV-2 TCID₅₀ was observed after irradiation with the UV-C 120 LED light at 3.4 mJ/cm² (10 cm, 5 s). These performances were in line with another study, in 121 122 which a 3.5-log₁₀ decrease was observed after irradiation with comparable UV-C doses [8]. 123 Another study, by Inagaki et al., demonstrated comparable UV-C LED performances with a 3-124 log₁₀ reduction in SARS-CoV-2 TCID₅₀ after 10 sec of irradiation at 2 cm using a deep UV-C 125 LED (280 nm) [5]. Interestingly, SARS-CoV-2 inactivation on a plastic surface was more efficient with the mercury UV-C lamp than with the LED UV-C lamp, even when considering 126 127 similar UV-C doses (p<0.0001). This could be due to the germicidal effect of ozone [7], 128 produced after O₂ irradiation at 185 nm with the low-pressure mercury lamp [13].

129

130 This study is one of the first description of viral inactivation on steel and absorbent materials 131 by UV-C lamps. Interestingly, inactivation rates were lower on absorbent materials (tissue, 132 paper and cardboard: ≥ 99.8 %) than on plastic (> 99.999 %). This was probably because a 133 fraction of the inoculum (200 µL) was absorbed inside the materials and shielded from the UV-134 C light, which is less likely to happen with respiratory droplets (5 µL). SARS-CoV-2 135 inactivation rates on steel were above 99.9 % for each lamp. These inactivation rates were lower 136 than on plastic (99.999 %) but were probably underestimated due to a low viability of SARS-137 CoV-2 on steel (TCID₅₀ $< 4 \log_{10}/mL$).

138

The mercury UV-C lamp demonstrated a higher efficacy than the LED on a plastic surface. For this reason, the mercury UV-C lamp could be more relevant in high-risk settings, such as medical care or research laboratories. In contrast, the UV-C LED demonstrated good efficacy on steel and absorbent surfaces and has several advantages over the mercury lamp, especially a lower power consumption (18 mW *vs* 70 W) and a smaller size (3.5 *vs* 31 cm). In addition, its performance could probably be improved by combining several LEDs emitting at different 145 wavelengths. For these reasons, the LED could be especially interesting in industry or146 household applications.

147

148 STATEMENTS & DECLARATIONS

Funding statement: This study was funded by BICE45 (Saint-Ay, France), specialized in
electronic cards. This society also provided both lamps.

151 Competing interests: This research was funded by BICE45 (Saint-Ay, France), which is 152 specialized in electronic cards. This society also provided both lamps. Authors have no other 153 financial interests in BICE45.

154 Author contributions: All authors contributed to the study conception and design. Material

155 preparation, data collection and analysis were performed by both authors. Both authors wrote

156 and approved the final manuscript.

157 **Data availability**: Marlet, Julien (2021), "UV-C COVID", Mendeley Data, V1, doi:

158 10.17632/6gxgfgdfwc.1. https://data.mendeley.com/datasets/6gxgfgdfwc/1

159 Ethics approval, consent to participate and publication : Sample collection was approved

160 by the Ministère de l'Enseignement Supérieur et de la Recherche (authorization n° DC-2020-

161 3961). Informed consent was obtained from all subjects involved in the study.

162

163 **REFERENCES**

- 164 1. Doremalen N van, Bushmaker T, Morris DH, et al. Aerosol and Surface Stability of
- 165 SARS-CoV-2 as Compared with SARS-CoV-1. N Engl J Med. 2020; 382(16):1564–
 166 1567.
- 167 2. Hadi J, Dunowska M, Wu S, Brightwell G. Control Measures for SARS-CoV-2: A

168 Review on Light-Based Inactivation of Single-Stranded RNA Viruses. Pathogens. 2020;

169 9(9):737.

170	3.	Cutler TD, Zimmerman JJ. Ultraviolet irradiation and the mechanisms underlying its
171		inactivation of infectious agents. Anim Health Res Rev. 2011; 12(1):15–23.
172	4.	Heilingloh CS, Aufderhorst UW, Schipper L, et al. Susceptibility of SARS-CoV-2 to
173		UV irradiation. American Journal of Infection Control. 2020; 48(10):1273–1275.
174	5.	Inagaki H, Saito A, Sugiyama H, Okabayashi T, Fujimoto S. Rapid inactivation of
175		SARS-CoV-2 with deep-UV LED irradiation. Emerg Microbes Infect. 2020; 9(1):1744–
176		1747.
177	6.	Storm N, McKay LGA, Downs SN, et al. Rapid and complete inactivation of SARS-
178		CoV-2 by ultraviolet-C irradiation. Sci Rep. 2020; 10(1):22421.
179	7.	Criscuolo E, Diotti RA, Ferrarese R, et al. Fast inactivation of SARS-CoV-2 by UV-C
180		and ozone exposure on different materials. Emerging Microbes & Infections. 2021;
181		10(1):206–210.
182	8.	Ma B, Gundy PM, Gerba CP, Sobsey MD, Linden KG. UV Inactivation of SARS-CoV-
183		2 across the UVC Spectrum: KrCl* Excimer, Mercury-Vapor, and Light-Emitting-Diode
184		(LED) Sources. Dudley EG, editor. Appl Environ Microbiol. 2021; 87(22):e01532-21.
185	9.	Reed LJ, Muench H. A SIMPLE METHOD OF ESTIMATING FIFTY PER CENT
186		ENDPOINTS12. American Journal of Epidemiology. 1938; 27(3):493–497.
187	10.	Boegel SJ, Gabriel M, Sasges M, et al. Robust Evaluation of Ultraviolet-C Sensitivity
188		for SARS-CoV-2 and Surrogate Coronaviruses. Microbiol Spectr. 2021; 9(2):e00537-21.
189	11.	Biasin M, Bianco A, Pareschi G, et al. UV-C irradiation is highly effective in
190		inactivating SARS-CoV-2 replication. Sci Rep. 2021; 11:6260.

191	12.	Sabino CP, Sellera FP, Sales-Medina DF, et al. UV-C (254 nm) lethal doses for SARS-
192		CoV-2. Photodiagnosis Photodyn Ther. 2020; 32:101995.
193	13.	Claus H. Ozone Generation by Ultraviolet Lamps. Photochem Photobiol. 2021;
194		97(3):471–476.
195		

196

197 Figure 1: SARS-CoV-2 inactivation on plastic by mercury and LED UV-C lamps

198 A) SARS-CoV-2 TCID₅₀ depending on the dose of UV-C received after irradiation on a plastic 199 surface by the mercury lamp (plain black circles) or the LED (empty red circles). Empty black 200 circles, non-irradiated control sample. Red curve represents the non-linear regression by 201 exponential two phases decay for the LED. B) SARS-CoV-2 inactivation rates by UV-C lamps 202 on a plastic surface depending on the duration (5 to 60 s) and the distance of irradiation. 203 Distance of 10, 5 and 3 cm are represented with white/grey/black bars for the mercury lamp 204 and white/orange/red dotted bars for the LED. Results are represented as mean with standard 205 deviation for both panels. *, p < 0.05; **, p < 0.01.

206

Figure 2: SARS-CoV-2 inactivation on steel, tissue, paper and cardboard by mercury and LED UV-C lamps

A) SARS-CoV-2 TCID₅₀ depending on the dose of UV-C received after irradiation on steel
(diamonds), tissue (circles), paper (squares) or cardboards (triangles) surfaces by the mercury
lamp (plain symbols) or the LED (empty symbols). B) SARS-CoV-2 inactivation rates by UVC lamps at 3 cm depending on the irradiated surface (steel, tissue, paper or cardboard) and the
duration of irradiation. Durations of 15, 30 and 60 s are represented with white/grey/black bars

- for the mercury lamp and white/orange/red dotted bars for the LED. Results are represented as
- 215 mean with standard deviation for both panels. **, p < 0.01; ***, p < 0.001; ****, p < 0.0001.



FIG 1A



FIG1B



FIG2A



FIG2B